

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 1                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Valvoline™ High Performance SAE 85W-140 Gear Oil

### Recommended use of the chemical and restrictions on use

|                                                                                                                                                                                 |                                                                                                                                                                      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Details of the supplier of the safety data sheet</b><br><br>Valvoline LLC<br>3499 Blazer Parkway<br>Lexington, KY 40509<br>United States of America<br><br>SDS@valvoline.com | <b>Emergency telephone number</b><br>1-800-VALVOLINE<br><br><b>Regulatory Information Number</b><br>1-800-TEAMVAL<br><br><b>Product Information</b><br>1-800-TEAMVAL |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Skin irritation : Category 2  
  
Eye irritation : Category 2A  
  
Skin sensitization : Category 1

### GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wash skin thoroughly after handling.  
Contaminated work clothing must not be allowed out of the

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 2                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

workplace.

Wear eye protection/ face protection.

Wear protective gloves.

**Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

| Chemical Name                                 | CAS-No.    | Classification                                                         | Concentration (%) |
|-----------------------------------------------|------------|------------------------------------------------------------------------|-------------------|
| RESIDUAL OILS (PETROLEUM),<br>SOLVENT-DEWAXED | 64742-62-7 | Not a hazardous<br>substance or mixture.                               | 94.92             |
| MINERAL OIL                                   |            | Not a hazardous<br>substance or mixture.                               | 1.39              |
| ALKYL PHOSPHATE                               |            | Skin Corr. 1B; H314<br><br>Eye Dam. 1; H318<br><br>STOT SE 3; H335     | 1.02              |
| LONG-CHAIN ALKYL AMINE                        |            | Acute Tox. 4; H302<br><br>Acute Tox. 2; H330<br><br>Acute Tox. 3; H311 | 0.34              |

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 3                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

|  |  |                                                                                                                                      |  |
|--|--|--------------------------------------------------------------------------------------------------------------------------------------|--|
|  |  | Skin Corr. 1B; H314<br><br>Eye Dam. 1; H318<br><br>Skin Sens. 1; H317<br><br>Aquatic Acute 1; H400<br><br>Aquatic Chronic 1;<br>H410 |  |
|--|--|--------------------------------------------------------------------------------------------------------------------------------------|--|

#### SECTION 4. FIRST AID MEASURES

|                                                             |                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice                                              | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.                                                                                                                                                                                                                                  |
| If inhaled                                                  | : If breathed in, move person into fresh air.<br>If unconscious place in recovery position and seek medical advice.<br>If symptoms persist, call a physician.                                                                                                                                                                                                     |
| In case of skin contact                                     | : Remove contaminated clothing. If irritation develops, get medical attention.<br>If on skin, rinse well with water.<br>Wash contaminated clothing before re-use.                                                                                                                                                                                                 |
| In case of eye contact                                      | : Immediately flush eye(s) with plenty of water.<br>Remove contact lenses.<br>Protect unharmed eye.                                                                                                                                                                                                                                                               |
| If swallowed                                                | : Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.                                                                                                                                                                                                                    |
| Most important symptoms and effects, both acute and delayed | : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:<br>stomach or intestinal upset (nausea, vomiting, diarrhea)<br>irritation (nose, throat, airways)<br>Dizziness<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation. |
| Notes to physician                                          | : No hazards which require special first aid measures.                                                                                                                                                                                                                                                                                                            |

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 4                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
Oxides of phosphorus
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 5                   |
| SAFETY DATA SHEET                                                                 |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

| Components                                        | CAS-No.    | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis           |
|---------------------------------------------------|------------|----------------------------------|---------------------------------------------------|-----------------|
| RESIDUAL OILS<br>(PETROLEUM), SOLVENT-<br>DEWAXED | 64742-62-7 | PEL                              | 500 ppm<br>2,000 mg/m3                            | OSHA_TRA<br>NS  |
|                                                   |            | REL                              | 5 mg/m3<br>Mist.                                  | NIOSH/GUID<br>E |
|                                                   |            | STEL                             | 10 mg/m3<br>Mist.                                 | NIOSH/GUID<br>E |
|                                                   |            | PEL                              | 5 mg/m3<br>Mist.                                  | OSHA_TRA<br>NS  |
| MINERAL OIL                                       |            | REL                              | 5 mg/m3<br>Mist.                                  | NIOSH/GUID<br>E |
|                                                   |            | STEL                             | 10 mg/m3<br>Mist.                                 | NIOSH/GUID<br>E |
|                                                   |            | PEL                              | 5 mg/m3<br>Mist.                                  | OSHA_TRA<br>NS  |

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 6                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

|  |  |     |                                |        |
|--|--|-----|--------------------------------|--------|
|  |  | TWA | 5 mg/m3<br>Mist.               | TN OEL |
|  |  | TWA | 5 mg/m3<br>Inhalable fraction. | ACGIH  |

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:  
impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 600.01 °F / 315.56 °C  
(1,013.333333 hPa)  
Calculated Phase Transition Liquid/Gas

Flash point : > 390 °F / > 199 °C  
Method: Cleveland open cup

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 7                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br>VV825                         |  | Version: 1.2              |

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Evaporation rate                       | : No data available                            |
| Flammability (solid, gas)              | : No data available                            |
| Upper explosion limit                  | : 7 %(V)<br>Calculated Explosive Limit         |
| Lower explosion limit                  | : 0.9 %(V)<br>Calculated Explosive Limit       |
| Vapour pressure                        | : 0.1 hPa (20 °C)<br>Calculated Vapor Pressure |
| Relative vapour density                | : No data available                            |
| Relative density                       | : No data available                            |
| Density                                | : 0.9040 g/cm3 (15.56 °C)                      |
| Solubility(ies)                        |                                                |
| Water solubility                       | : No data available                            |
| Solubility in other solvents           | : No data available                            |
| Partition coefficient: n-octanol/water | : No data available                            |
| Thermal decomposition                  | : No data available                            |
| Viscosity                              |                                                |
| Viscosity, dynamic                     | : No data available                            |
| Viscosity, kinematic                   | : 394 mm2/s (40 °C)                            |
| Oxidizing properties                   | : No data available                            |

---

## SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| Reactivity                         | : No decomposition if stored and applied as directed. |
| Chemical stability                 | : Stable under recommended storage conditions.        |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization.  |
| Incompatible materials             | : Strong oxidizing agents                             |
| Hazardous decomposition products   | carbon dioxide and carbon monoxide                    |

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 8                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

LD 50 (Rabbit): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

LONG-CHAIN ALKYL AMINE:

Acute oral toxicity :  
Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 2.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

### Skin corrosion/irritation

Causes skin irritation.

#### Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

#### Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 9                   |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

Result: Not irritating to skin

**MINERAL OIL:**

Result: Mildly irritating to skin

**ALKYL PHOSPHATE:**

Result: Corrosive to skin

**LONG-CHAIN ALKYL AMINE:**

Result: Corrosive after 3 minutes to 1 hour of exposure

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: Not irritating to eyes

**MINERAL OIL:**

Result: Mildly irritating to eyes

**ALKYL PHOSPHATE:**

Result: Corrosive to eyes

**LONG-CHAIN ALKYL AMINE:**

Result: Corrosive to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

**LONG-CHAIN ALKYL AMINE:**

Assessment: May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**Components:**

|                                                                                   |                           |
|-----------------------------------------------------------------------------------|---------------------------|
|  | Page: 10                  |
| SAFETY DATA SHEET                                                                 | Revision Date: 07/31/2016 |
|                                                                                   | Print Date: 11/1/2016     |
|                                                                                   | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br>VV825                         | Version: 1.2              |

**ALKYL PHOSPHATE:**

Assessment: May cause respiratory irritation.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

No aspiration toxicity classification

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 11                  |
| SAFETY DATA SHEET                                                                 |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     |  | Version: 1.2              |

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

#### LONG-CHAIN ALKYL AMINE:

##### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

#### Persistence and degradability

##### Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### Bioaccumulative potential

##### Components:

No data available

##### Mobility in soil

##### Components:

No data available

##### Other adverse effects

No data available

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

##### Components:

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 12                  |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil                                  |  | Version: 1.2              |
| VV825                                                                             |  |                           |

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- General advice : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

## SECTION 14. TRANSPORT INFORMATION

### International transport regulations

#### REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|           |                      |               |                    |               |                              |

#### U.S. DOT - ROAD

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### CFR\_RAIL\_C

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### U.S. DOT - INLAND WATERWAYS

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### TDG\_ROAD\_C

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### TDG\_RAIL\_C

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### TDG\_INWT\_C

|                     |
|---------------------|
| Not dangerous goods |
|---------------------|

|                                                                                   |                           |
|-----------------------------------------------------------------------------------|---------------------------|
|  | Page: 13                  |
| SAFETY DATA SHEET                                                                 | Revision Date: 07/31/2016 |
|                                                                                   | Print Date: 11/1/2016     |
|                                                                                   | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                     | Version: 1.2              |

#### INTERNATIONAL MARITIME DANGEROUS GOODS

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

|                     |
|---------------------|
| Not dangerous goods |
|                     |

#### MX\_DG

|                     |
|---------------------|
| Not dangerous goods |
|                     |

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

|                  |    |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313 Component(s)SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

##### Pennsylvania Right To Know

|                                               |              |                     |
|-----------------------------------------------|--------------|---------------------|
| RESIDUAL OILS (PETROLEUM),<br>SOLVENT-DEWAXED | 64742-62-7   | 90.00 -<br>100.00 % |
| LUBRICANT ADDITIVE                            | Not Assigned | 5.00 - 10.00 %      |

##### New Jersey Right To Know

|                                               |              |                     |
|-----------------------------------------------|--------------|---------------------|
| RESIDUAL OILS (PETROLEUM),<br>SOLVENT-DEWAXED | 64742-62-7   | 90.00 -<br>100.00 % |
| LUBRICANT ADDITIVE                            | Not Assigned | 5.00 - 10.00 %      |
| HEAVY PARAFFINIC DISTILLATE                   | 64742-54-7   | 1.00 - 5.00 %       |

|                                                                                   |  |                           |
|-----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 14                  |
| <b>SAFETY DATA SHEET</b>                                                          |  | Revision Date: 07/31/2016 |
|                                                                                   |  | Print Date: 11/1/2016     |
|                                                                                   |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br>VV825                         |  | Version: 1.2              |

|                                                           |              |               |
|-----------------------------------------------------------|--------------|---------------|
| MINERAL OIL                                               | Not Assigned | 1.00 - 5.00 % |
| ALKYL PHOSPHATE                                           | Not Assigned | 1.00 - 5.00 % |
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0   | 0.10 - 1.00 % |

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

|       |                                                           |
|-------|-----------------------------------------------------------|
| TSCA  | : On TSCA Inventory                                       |
| DSL   | : All components of this product are on the Canadian DSL. |
| AUSTR | : On the inventory, or in compliance with the inventory   |
| ENCS  | : On the inventory, or in compliance with the inventory   |
| KECL  | : On the inventory, or in compliance with the inventory   |
| PICCS | : On the inventory, or in compliance with the inventory   |
| IECSC | : On the inventory, or in compliance with the inventory   |

**Inventories**


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

|                                                                                   |                           |
|-----------------------------------------------------------------------------------|---------------------------|
|  | Page: 15                  |
| SAFETY DATA SHEET                                                                 | Revision Date: 07/31/2016 |
|                                                                                   | Print Date: 11/1/2016     |
|                                                                                   | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br>VV825                         | Version: 1.2              |

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 07/31/2016

| NFPA:                                                                                                                                                         | HMIS III:                                                                                                                                                                                                                                                                                        |               |          |                     |          |                        |          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|---------------------|----------|------------------------|----------|
| <p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p> | <table border="1"> <tr> <td><b>HEALTH</b></td><td><b>1</b></td></tr> <tr> <td><b>FLAMMABILITY</b></td><td><b>1</b></td></tr> <tr> <td><b>PHYSICAL HAZARD</b></td><td><b>0</b></td></tr> </table> <p>0 = not significant, 1 = Slight,<br/>2 = Moderate, 3 = High<br/>4 = Extreme, * = Chronic</p> | <b>HEALTH</b> | <b>1</b> | <b>FLAMMABILITY</b> | <b>1</b> | <b>PHYSICAL HAZARD</b> | <b>0</b> |
| <b>HEALTH</b>                                                                                                                                                 | <b>1</b>                                                                                                                                                                                                                                                                                         |               |          |                     |          |                        |          |
| <b>FLAMMABILITY</b>                                                                                                                                           | <b>1</b>                                                                                                                                                                                                                                                                                         |               |          |                     |          |                        |          |
| <b>PHYSICAL HAZARD</b>                                                                                                                                        | <b>0</b>                                                                                                                                                                                                                                                                                         |               |          |                     |          |                        |          |

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### Full text of H-Statements referred to under sections 2 and 3.

|      |                                                       |
|------|-------------------------------------------------------|
| H302 | Harmful if swallowed.                                 |
| H311 | Toxic in contact with skin.                           |
| H314 | Causes severe skin burns and eye damage.              |
| H317 | May cause an allergic skin reaction.                  |
| H318 | Causes serious eye damage.                            |
| H330 | Fatal if inhaled.                                     |
| H335 | May cause respiratory irritation.                     |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |

### Further information

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

|                                                                                  |  |                           |
|----------------------------------------------------------------------------------|--|---------------------------|
|  |  | Page: 16                  |
| <b>SAFETY DATA SHEET</b>                                                         |  | Revision Date: 07/31/2016 |
|                                                                                  |  | Print Date: 11/1/2016     |
|                                                                                  |  | SDS Number: R0173308      |
| Valvoline™ High Performance SAE 85W-140 Gear Oil<br><br>VV825                    |  | Version: 1.2              |

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System